

*Our highest quality solvent, emulsifying stripper. Quickly and effectively removes both metal-linked and zinc-free floor finishes. Highly dilutable, low odor and no-rinse.*



### Where To Use

All types of resilient floors:

Vinyl Tile	Asbestos Tile	Asphalt Tile
Linoleum	Terrazzo	Concrete

### Dilution

Heavy stripping – 1/4 (32 oz./gallon)  
Medium – 1/8 (16 oz./gallon)  
Light – 1/16 (8 oz./gallon)

### Directions

Dust mop and scrape gum, etc. from floor. Determine dilution from table above and add appropriate amount of product to cool or room temperature water.. Apply solution generously to a workable area. Allow solution to sit for 5-10 minutes. Floor must remain wet. Agitate solution with floor machine using an aggressive stripping pad (black or brown). If needed, hand scrub edges and corners with edge pad or center of the scrubbing pad. Remove old finish and stripping solution with mop or wet vac. Inspect entire floor to ensure stripping has been complete. Reapply to areas that require additional stripping and pick up solution. Allow floor to dry completely prior to applying sealer or finish. Rinsing is not necessary but ensures a good clean, residue-free floor.

### Technical Specifications

COLOR: ..... Transparent, red	VISCOSITY: ..... Water Thin
FORM: ..... Liquid	STORAGE(Unopened):..1 Year @R.T.
SCENT: ..... Rose	BIODEGRADABLE: ...Yes
pH: ..... 12 - 13.4	WEIGHT/GAL: .....8.0
FLASH POINT: > 200° F	SHIPPING CLASS: .....None
FOAM: ..... Low	PACKAGING: .....4x1, 5 gal, 55 gal
TYPE: ..... No Rinse, Floor Finish Stripper	

