

The latest in polymer floor sealer/finish formulations. Highest initial shine, extremely responsive, excellent in no maintenance floor finish programs. High solid content.



Where To Use

Programs where high quality, gloss and durability are a must.

- | | | |
|------------|---------------|-------------|
| Terrazzo | Concrete | Rubber Tile |
| Vinyl Tile | Ceramic Tile | Sealed Wood |
| Linoleum | Asbestos Tile | |

Dilution

As is.

Directions

Ensure that the floor has been completely stripped of all old finish, scrubbed or cleaned. Follow stripping procedure from the Simoniz® Floor Care Manual. The floor should be completely dry before applying the first coat and all subsequent coats. Apply in thin coats, evenly. If the floor is old or in poor condition, two coats of Simoniz® Super Sealer are recommended. On unsealed floors, apply 4 coats. On cleaned or scrubbed floors apply as needed. Be sure to use a different mop for stripping, sealing and finish. Allow 24 hours for curing before burnishing. For superior results, use with regular weekly UHS burnishing with an aggressive pad.

Technical Specifications

COLOR: Milk-white	TYPE: Acrylic Polymer Sealer/Finsh
FORM: Liquid	SOLID CONTENT: 25%
SCENT: Mild Solvent/Polymer	INITIAL GLOSS: Excellent
pH: 8.0	RECOAT DRYING TIME: 20 - 30 Minutes
FLASH POINT: None	COVERAGE: 2500 sq. ft.
FOAM: None	LEVELING: Excellent
VISCOSITY: Water Thin	SLIP COEFFIECIENT: 0.6
STORAGE(Unopened): . 1 Year @R.T.	REMOVABILITY: Excellent
BIODEGRADABLE: Yes	SCUFF RESISTANCE: Excellent
WEIGHT/GAL: 8.5	DETERGENT RESISTANT: Excellent
SHIPPING CLASS: None	HIGH SPEED BURNISH: Yes
PACKAGING: 4x1, 5 gal	

